

AHD-40A130



| Model . | AHD-40A130 |
|---------------------|---|
| Camera | |
| Image Sensor | SONY |
| DSP | TP2801 |
| Image Resolution | PAL: 25fps@960P(1280x960); NTSC: 30fps@960P(1280x960) |
| Effective Pixels | 1280(H)x960(V),1.3MP |
| TV System | PAL/NTSC |
| Electronic Shutter | 1/25s~1/50,000s , 1/30s~1/60,000s |
| Sync System | Internal |
| Usable Illumination | 0.001Lux |
| S/N Ratio | 50dB |
| Scanning System | Progressive Scan |
| Video Output Mode | AHD/CVBS (960H) (BNC) |
| Lens | |
| Focus Length | 2.8-12mm |
| Focus Control | Manual |
| Lens Type | Manual |
| Pixels | 2M Pixels |
| Night Vision | |

Design and Specifications are subject to change without notice

| | |
|------------------------|-------------------------|
| Infrared LED | ϕ 5X42PCS |
| Infrared Distance | 40M |
| IR Status | Under 10 Lux by CDS |
| IR Power On | CDS Auto Control |
| Camera Features | |
| Noise Reduction | 3D NR |
| OSD Support | Yes |
| General | |
| Weatherproof Housing | YES, IP66 |
| Anti-cut Bracket | YES, 3-Axis |
| Dual Voltage | NO |
| IR Cut Filter | YES |
| Heater | NO |
| Operation Temperature | -10°C ~ +50°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 700mA |
| Dimension | 295(W)x105(H)x95(D)mm |
| Weight | 1.7Kg |



ATTENZIONE

- Utilizzare sempre alimentatori adatti alle caratteristiche della telecamera e verificare che le polarità di cablaggio siano corrette.
- Verificare sempre la messa a terra degli impianti per evitare danneggiamenti dovuti a fulmini.
- Non utilizzare la telecamera in condizioni di umidità e/o temperatura non conformi a quanto dichiarato nella scheda tecnica
- Non installare la telecamera vicino a radiatori o fonti di calore
- Non puntare la telecamera contro Sole oppure contro forti sorgenti luminose che potrebbero danneggiare il CMOS

Design and Specifications are subject to change without notice